
## **SMB Bearings**

## **Radial Ball Bearing**

## Part Number: 16001



(for illustration only)



Material (rings & balls)	SAE52100 chrome steel				
Material (cage)	pressed steel				
Closures	None				
Load rating (stat)	211 Kgf				
Load rating (dyn)	459 Kgf				
Speed Limit *	31,000 rpm				
Standard Lubrication **	Aeroshell Fluid 12 oil				

\* with adequate lubrication

\*\* may vary

These bearings comply with EU ROHS and REACH regulations.

RADIAL PLAY	C2	CN		C3	C4	]	
(microns)	0 - 9	3 - 18		11 - 25	18 - 33	18 - 33	
TOLERANCE	P0		P6			P5	
Bore Deviation	+0 / -0.008mm		+0 / -0.007mm		+0 / -0	+0 / -0.005mm	
OD Deviation	+0 / -0.009mm		+0 / -0.008mm		+0 / -0	+0 / -0.006mm	
Width Deviation	+0 / -0.120mm		+0 / -0.120mm		+0 / -0	+0 / -0.040mm	
Single Bore Variation	8		7		2	4	
Single OD Variation	9		8		4	5	
Inner Width Variation	20		20		4	5	
Outer Width Variation	20		20		4	5	
Inner Radial Runout	10		7		4	4	
Outer Radial Runout	15		9		e	5	

SMB Bearings take no responsibility for any errors or omissions in this data sheet. We reserve the right to change specifications without prior notice. We recommend that adequate testing is carried out on products before they are determined as suitable for an application.