
## **SMB Bearings**

## **Radial Ball Bearing**

## Part Number: 16005ZZ



(for illustration only)



**Inner Radial Runout** 

**Outer Radial Runout** 

Material (rings & balls)	SAE52100 chrome steel			
Material (cage)	pressed steel			
Closures	Metal shields			
Load rating (stat)	549 Kgf			
Load rating (dyn)	933 Kgf			
Speed Limit *	15,000 rpm			
Standard Lubrication **	Kyodo Yushi Multemp SRL grease			

\* with adequate lubrication

\*\* may vary

8

10

These bearings comply with EU ROHS and REACH regulations.

4

7

	RADIAL PLAY	C2	2 CI		C3	C4		
	(microns)	1 - 11	5 -	20	13 - 28	23 - 41		
		-	•					
TOLERANCE		PO		P6			P5	
<b>Bore Deviation</b>		+0 / -0.010mm		+0 / -0.008mm		+0 / -0	+0 / -0.006mm	
<b>OD</b> Deviation		+0 / -0.011mm		+0 / -0.009mm		+0 / -0	+0 / -0.007mm	
Width Deviation		+0 / -0.120mm		+0 / -0.120mm		+0 / -0	+0 / -0.040mm	
Single Bore Variation		10	10		8	:	5	
Single OD Variation 16		13			5			
Inner Width Variation 20		20			5			
<b>Outer Width Variation</b>		20		20		:	5	

SMB Bearings take no responsibility for any errors or omissions in this data sheet. We reserve the right to change specifications without prior notice. We recommend that adequate testing is carried out on products before they are determined as suitable for an application.

13

20