
SMB Bearings

Radial Ball Bearing

Part Number: 16101-2RS



(for illustration only)



Material (rings & balls)	SAE52100 chrome steel			
Material (cage)	pressed steel			
Closures	Rubber contact seals			
Load rating (stat)	312 Kgf			
Load rating (dyn)	693 Kgf			
Speed Limit *	17,400 rpm			
Standard Lubrication **	Kyodo Yushi Multemp SRL grease			

* with adequate lubrication

** may vary

These bearings comply with EU ROHS and REACH regulations.

RADIAL PLAY	C2	C	N	С3	C4		
(microns)	0 - 9	3 - 18		11 - 25	18 - 33	18 - 33	
TOLERANCE	P0		P6			P5	
Bore Deviation	+0 / -0.008mm		+0 / -0.007mm		+0 / -0	+0 / -0.005mm	
OD Deviation	+0 / -0.009mm		+0 / -0.008mm		+0 / -0	+0 / -0.006mm	
Width Deviation	+0 / -0.120mm		+0 / -0.120mm		+0 / -0	+0 / -0.040mm	
Single Bore Variation	8		7		2	4	
Single OD Variation	12		10		4	5	
Inner Width Variation	20		20			5	
Outer Width Variation	20		20		4	5	
Inner Radial Runout	10		7		4	4	
Outer Radial Runout	15		9		e	5	

SMB Bearings take no responsibility for any errors or omissions in this data sheet. We reserve the right to change specifications without prior notice. We recommend that adequate testing is carried out on products before they are determined as suitable for an application.