
## **SMB Bearings**

## **Radial Ball Bearing**

## Part Number: 6002-2RS



(for illustration only)



Material (rings & balls)	SAE52100 chrome steel			
Material (cage)	pressed steel			
Closures	Rubber contact seals			
Load rating (stat)	290 Kgf			
Load rating (dyn)	570 Kgf			
Speed Limit *	16,200 rpm			
Standard Lubrication **	Kyodo Yushi Multemp SRL greas			

\* with adequate lubrication

\*\* may vary

These bearings comply with EU ROHS and REACH regulations.

RADIAL PLAY	C2	CN		C3	C4			
(microns)	0 - 9	3 - 18		11 - 25	18 - 33			
TOLERANCE	PO		P6		]	P5		
Bore Deviation	+0 / -0.008mm		+0 / -0.007mm		+0 / -0	+0 / -0.005mm		
OD Deviation	+0 / -0.011mm		+0 / -0.009mm		+0 / -0	+0 / -0.007mm		
Width Deviation	+0 / -0.120mm		+0 / -0.120mm		+0 / -0	+0 / -0.040mm		
Single Bore Variation	8		7		4	4		
Single OD Variation	16		13		4	5		
Inner Width Variation	20		20		4	5		
Outer Width Variation	20		20		5	5		
Inner Radial Runout	10		7		4	4		
Outer Radial Runout	20		10		7	7		

SMB Bearings take no responsibility for any errors or omissions in this data sheet. We reserve the right to change specifications without prior notice. We recommend that adequate testing is carried out on products before they are determined as suitable for an application.