
## **SMB Bearings**

## **Radial Ball Bearing**

## Part Number: 6005ZZ



(for illustration only)



**Outer Radial Runout** 

Material (rings & balls)	SAE52100 chrome steel				
Material (cage)	pressed steel				
Closures	Metal shields				
Load rating (stat)	597 Kgf				
Load rating (dyn)	1026 Kgf				
Speed Limit *	15,000 rpm				
Standard Lubrication **	Kyodo Yushi Multemp SRL grease				

\* with adequate lubrication

\*\* may vary

These bearings comply with EU ROHS and REACH regulations.

7

RADIAL PLAY	C2	CN		C3	C4		
(microns)	1 - 11	5 - 20		13 - 28	23 - 41		
		-			_		
TOLERANCE	P0		P6		]	P5	
<b>Bore Deviation</b>	+0 / -0.010mm		+0 / -0.008mm		+0 / -0	+0 / -0.006mm	
<b>OD</b> Deviation	+0 / -0.011mm		+0 / -0.009mm		+0 / -0	+0 / -0.007mm	
Width Deviation	+0 / -0.120mm		+0 / -0.120mm		+0 / -0	+0 / -0.040mm	
Single Bore Variation	10		8		4	5	
Single OD Variation	16		13		4	5	
Inner Width Variation	20		20		4	5	
<b>Outer Width Variation</b>	20		20		4	5	
Inner Radial Runout	13		8		4	4	

SMB Bearings take no responsibility for any errors or omissions in this data sheet. We reserve the right to change specifications without prior notice. We recommend that adequate testing is carried out on products before they are determined as suitable for an application.

10

20