
## **SMB Bearings**

## **Radial Ball Bearing**

## Part Number: 6006ZZ



(for illustration only)



Material (rings & balls)	SAE52100 chrome steel			
Material (cage)	pressed steel			
Closures	Metal shields			
Load rating (stat)	843 Kgf			
Load rating (dyn)	1349 Kgf			
Speed Limit *	13,000 rpm			
Standard Lubrication **	Kyodo Yushi Multemp SRL grease			

\* with adequate lubrication

\*\* may vary

These bearings comply with EU ROHS and REACH regulations.

RADIAL PLAY	C2	C	N	C3	C4			
(microns)	1 - 11	5 - 20		13 - 28	23 - 41			
TOLERANCE	PO		P6		]	P5		
<b>Bore Deviation</b>	+0 / -0.010mm		+0 / -0.008mm		+0 / -0	+0 / -0.006mm		
OD Deviation	+0 / -0.013mm		+0 / -0.011mm		+0 / -0	+0 / -0.009mm		
Width Deviation	+0 / -0.120mm		+0 / -0.120mm		+0 / -0	+0 / -0.040mm		
Single Bore Variation	10		8		4	5		
Single OD Variation	13		11		7	7		
Inner Width Variation	20		20		4	5		
Outer Width Variation	20		20		5	5		
Inner Radial Runout	13		8		4	4		
Outer Radial Runout	25		13		8	8		

SMB Bearings take no responsibility for any errors or omissions in this data sheet. We reserve the right to change specifications without prior notice. We recommend that adequate testing is carried out on products before they are determined as suitable for an application.