
Radial Ball Bearing

Part Number: 6201-2RS





(for illustration only)

| Material (rings & balls) | SAE52100 chrome steel | | |
|----------------------------|-----------------------------------|--|--|
| Material (cage) | pressed steel | | |
| Closures | Rubber contact seals | | |
| Load rating (stat) | 312 Kgf | | |
| Load rating (dyn) | 693 Kgf | | |
| Speed Limit * | 16,200 rpm | | |
| Standard Lubrication ** | Kyodo Yushi Multemp SRL grease | | |

^{*} with adequate lubrication

These bearings comply with EU ROHS and REACH regulations.

| RADIAL PLAY | C2 | CN | С3 | C4 |
|-------------|------|--------|---------|---------|
| (microns) | 0 -9 | 3 - 18 | 11 - 25 | 18 - 33 |

| TOLERANCE | P0 | P6 | P5 |
|-----------------------|---------------|---------------|---------------|
| Bore Deviation | +0 / -0.008mm | +0 / -0.007mm | +0 / -0.005mm |
| OD Deviation | +0 / -0.01mm | +0 / -0.009mm | +0 / -0.007mm |
| Width Deviation | +0 / -0.120mm | +0 / -0.120mm | +0 / -0.080mm |
| Single Bore Variation | 6 | 5 | 4 |
| Single OD Variation | 16 | 13 | 5 |
| Inner Width Variation | 20 | 20 | 5 |
| Outer Width Variation | 20 | 20 | 5 |
| Inner Radial Runout | 10 | 7 | 4 |
| Outer Radial Runout | 15 | 9 | 6 |

SMB Bearings take no responsibilty for any errors or omissions in this data sheet. We reserve the right to change specifications without prior notice. We recommend that adequate testing is carried out on products before they are determined as suitable for an application.

^{**} may vary