
## Radial Ball Bearing

## Part Number: 6911





(for illustration only)

| Material<br>(rings & balls) | SAE52100<br>chrome steel  |  |  |
|-----------------------------|---------------------------|--|--|
| Material (cage)             | pressed steel             |  |  |
| Closures                    | None                      |  |  |
| Load rating (stat)          | 1410 Kgf                  |  |  |
| Load rating (dyn)           | 1660 Kgf                  |  |  |
| Speed Limit *               | 9,600 rpm                 |  |  |
| Standard<br>Lubrication **  | Aeroshell Fluid 12<br>oil |  |  |

<sup>\*</sup> with adequate lubrication

These bearings comply with EU ROHS and REACH regulations.

| RADIAL PLAY | C2     | CN     | С3      | C4      |
|-------------|--------|--------|---------|---------|
| (microns)   | 1 - 15 | 8 - 28 | 23 - 43 | 38 - 61 |

| TOLERANCE             | P0            | P6            | P5            |  |
|-----------------------|---------------|---------------|---------------|--|
| Bore Deviation        | +0 / -0.015mm | +0 / -0.012mm | +0 / -0.009mm |  |
| OD Deviation          | +0 / -0.013mm | +0 / -0.011mm | +0 / -0.009mm |  |
| Width Deviation       | +0 / -0.150mm | +0 / -0.150mm | +0 / -0.150mm |  |
| Single Bore Variation | 19            | 15            | 9             |  |
| Single OD Variation   | 16            | 14            | 9             |  |
| Inner Width Variation | 25            | 25            | 6             |  |
| Outer Width Variation | 20            | 20            | 5             |  |
| Inner Radial Runout   | 20            | 10            | 5             |  |
| Outer Radial Runout   | 25            | 13            | 8             |  |

SMB Bearings take no responsibilty for any errors or omissions in this data sheet. We reserve the right to change specifications without prior notice. We recommend that adequate testing is carried out on products before they are determined as suitable for an application.

<sup>\*\*</sup> may vary