
## **Radial Ball Bearing**

## Part Number: CCZR-636-2PKS



(for illustration only)



| Material<br>(rings & balls) | Zirconium dioxide<br>(ZrO2)      |  |
|-----------------------------|----------------------------------|--|
| Material (cage)             | Full complement,<br>PEEK or PTFE |  |
| Closures                    | PEEK seals                       |  |
| Load rating (stat)          | 105 Kgf                          |  |
| Load rating (dyn)           | 149 Kgf                          |  |
| Speed Limit *               | 7,000 rpm                        |  |
| Standard<br>Lubrication **  | None                             |  |

<sup>\*</sup> with adequate lubrication

These bearings comply with EU ROHS and REACH regulations.

| RADIAL PLAY | C2    | CN     | С3     | C4      |
|-------------|-------|--------|--------|---------|
| (microns)   | 0 - 7 | 2 - 13 | 8 - 23 | 14 - 29 |

| TOLERANCE       | P0            |  |
|-----------------|---------------|--|
| Bore Deviation  | +0 / -0.008mm |  |
| OD Deviation    | +0 / -0.008mm |  |
| Width Deviation | +0 / -0.120mm |  |

SMB Bearings take no responsibilty for any errors or omissions in this data sheet. We reserve the right to change specifications without prior notice. We recommend that adequate testing is carried out on products before they are determined as suitable for an application.

<sup>\*\*</sup> may vary